

# Custom Made Timber Interior Door Care & Guarantee



## 5 Year Guarantee

We offer a **5-year guarantee** on our interior timber doors, provided the following conditions are met:

### Care & Handling

To ensure the longevity and performance of your custom timber interior doors, please follow these care and handling instructions:

#### Handling & Inspection

- Handle doors with care at all times.
- Inspect each door upon delivery for any damage or manufacturing defects before installation or finishing.

#### Storage Guidelines

- Store doors in a **dry, well-ventilated area**.
- Avoid placing doors directly on concrete floors or leaning them against freshly plastered (gib) walls.
- Keep doors out of direct sunlight prior to finishing, as UV exposure may cause discoloration or cracking.
- Timber is a natural material and may expand or contract with changes in temperature and humidity. To minimize movement, doors must be **sealed immediately upon delivery**.

#### Finishing Instructions

- All four edges and both faces of the door must be sealed using an **oil-based paint suitable for Abodo Vulcan timber**.
- Pay special attention to sealing the **top and bottom edges**, which are often overlooked but critical for moisture protection.

1. **All surfaces**—including the top and bottom edges—must be coated in accordance with the **paint manufacturer's recommendations**.
2. The **first coat** must be an **oil-based paint** specifically suitable for **Abodo Vulcan** timber.
3. Only use paints with a **Light Reflectance Value (LRV) of 40% or higher** to reduce heat absorption and surface stress.
4. **Cavity slider doors** must be stored **upright and away from direct sunlight** to prevent warping or uneven shading.